

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/512111

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
20 November 2003 (20.11.2003)

PCT

(10) International Publication Number  
WO 03/095259 A2

(51) International Patent Classification<sup>7</sup>: B60L

LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/US03/10327

(22) International Filing Date: 3 April 2003 (03.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/378,364 8 May 2002 (08.05.2002) US  
60/427,235 19 November 2002 (19.11.2002) US

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**  
— of inventorship (Rule 4.17(iv)) for US only

(71) Applicant and

(72) Inventor: FENG, Zhide [CA/US]; 1919 Atlas ct., Troy, MI 48083 (US).

**Published:**

— without international search report and to be republished upon receipt of that report

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AUXILIARY BRAKE CONTROL SYSTEM

(57) **Abstract:** An easy-installed auxiliary brake control system for driving practice of an automobile by means of an auxiliary brake actuator and two-component cables. The cables have an outer sheath portion and an inner cable portion. It connects an auxiliary brake actuator to a brake arm of the automobile. The auxiliary brake actuator rests on a floor of a passenger compartment of the automobile, without necessity of being secured to it. When an instructor acts on the auxiliary brake actuator, the brake arm is actuated through relative movement between the inner cable portion and the outer sheath portion of the cables. This system is significantly cheaper than prior arts, especially for installation, and damages on the automobile for installation are minimized.

WO 03/095259 A2